




May 30, 2019

# TECHNICAL DATA REPORT

See SDS for complete safety/technical data



## VAPCO PART NO.

Part Number SCS-1 Size 2lb box 24/cs

# SEALING COMPOUND SLUGS

INSULATION/ SEALING

## DESCRIPTION

**SEALING COMPOUND SLUGS** are formulated and manufactured for use in many sealing, insulating and general maintenance applications. Will not stain, harden or dry and has excellent adhesion. May be painted. Each box contains two handy one pound slugs.

## FEATURES AND BENEFITS

- Flexible at -20°F
- Will Not Flow Below 350°F
- Odorless and Non-Corrosive
- Water and Vapor Proof
- For Use on Air Conditioners, Refrigerators and Freezers

## SPECIFICATIONS

**Appearance:** Off-white, putty-like solid | **Odor:** Faint, mild odor | **Flammability:** Not classified as a flammable hazard | **Specific Gravity:** 1.81 g/cm<sup>3</sup> | **Decomposition Temperature:** >200°C (392°F)

## LABEL INFORMATION

**SEALING COMPOUND SLUGS** are used for sealing, insulating and general application maintenance. Won't dry out, harden or stain. Keeps out dust, dirt and moisture. Pliable material easily manipulates to any form.

**DIRECTIONS:** Can be easily worked by hand into any desired shape. Simply press into place. Adheres to most clean, dry surfaces; including metal, wood, glass, masonry, plastic and rubber.

**FOR REFRIGERATORS AND FREEZERS:** Seal out air and moisture around tube entries, under latch plates, under hinges and over screw heads.

**FOR AIR CONDITIONERS:** Seal out air, dust and moisture around window openings, air ducts, seal adaptors and extensions.


**DANGERS: Read and understand the product's label and Safety Data Sheet.** May be harmful in contact with skin. Causes eye irritation. May cause cancer via inhalation of dust. May cause damage to organs (lungs) through prolonged or repeated exposure.



## CONTAINS

**SEALING COMPOUND SLUGS CONTAINS (CAS#) :** Limestone (1317-65-3), Butene, homopolymer (9003-27-4), Hydrous magnesium silicate (14807-96-6), Chlorite-group minerals (1318-59-8), Crystalline silica (impurity) (14808-60-7)

Health	0
Flammability	0
Reactivity	0
Personal	A



**WARNING:** This product can expose you to crystalline silica, which is known to the State of California to cause cancer. For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

## First Aid Measures

**Inhalation:** Not applicable.  
**Skin contact:** Remove from skin and wash with soap and water. Difficult to remove material may require the use of mineral spirits to remove residue. **Seek medical attention if irritation persists.**  
**Eye Contact:** Flush with water for 15-minutes. **Seek medical attention if irritation persists.**  
**Ingestion:** Do NOT induce vomiting. **Seek immediate medical attention.**

## Precautions

**Keep out of reach of children.** Wash hands or exposed areas thoroughly after handling and prior to eating, drinking or smoking. Use personal protective equipment. Safety glasses and gloves recommended to reduce exposure.

## Storage

**Keep out of reach of children.** Normal warehouse conditions are acceptable. Keep containers dry.

## In Case of Fire

For small fires use carbon dioxide (CO<sub>2</sub>), dry chemical or water spray. For large scale fires, use dry chemical, foam or water spray.

## Disposal

Dispose of in accordance with federal, state, and local regulations. Do not dispose material into any storm water or sewage system.